ASPEE HTP HORIZONTAL TRIPLEX PISTON POWER SPRAYER



CODE: PS/50

Suitable for large spraying operations in orchards, coffee plantation & field crops etc.

General Description:

ASPEE-HTP horizontal triplex power sprayer unit, Developing 400 PSI (28 Bar) pressure and giving free discharge of 50 LPM at 950 rpm supplied with pulley, pressure vessel, pressure gauge, By-pass cum pressure regulator valve, 3 meter long By-pass hose and suction hose with strainer, couplings for delivery hose.

Special Features:

- Heavy duty & efficient sprayer
- Triplex stainless steel piston and oil bath lubrication
- Develops 400 psi pressure
- Suction capacity 50 lit per minute at 950 rpm
- Light weight & compact construction
- Pressure regulator for spraying pressure
- · Convenient to spray with 4 to 5 spray gun at a time

ASPEE HTP HORIZONTAL TRIPLEX PISTON POWER SPRAYER



CODE: PS/50

Technical Description	
Model	PS/50
No. of piston	3
Suction capacity	50 ltr / min
Normal working pressure	200 psi (14 bar)
Max. pressure	400 (28 bar)
Pump revolution	950 rpm
Power	4 - 5 hp
L x W x H (in mm)	340 X 285 X 300
Weight (without oil & pulley)	12 kg (approx)



ASPEE House, P. O. Box No. 7602, B. J. Patel Road, Malad (W), Mumbai 400 064. India. Tel.: 91-22 6774 5700. Fax: 91-22 2882 2336. Email: aspee@aspee.net. Website: www.aspee.com Important Notes: Specifications Subject To Change Without Notice.

AN ISO 9001:2008 CERTIFIED COMPANY