

ASPEE ASP 767 HIGH PRESSURE KNAPSACK SPRAYER



CODE: UB001B/TU26

Suitable for row & ground crops like cotton, soyabean, vegetables, tea & coffee plantations, orchards & tall trees

General Description:

High density polyethylene tank 25 lit. capacity with clean out port, adjustable shoulder straps with cushion, 110 cm. long high pressure delivery hose, choice of spray gun. forced air cooled 25.6 cc petrol engine with reciprocating type metal pump & gear box.

Special Features:

- Economic for spraying costly pesticides
- Spray lance & spray gun supplied with sprayer
- Supplied with 25.6 cc engine
- Engine fitted with recoil starter for easy starting
- Prompt supply of spare parts & after sales services throughout the country
- Highly mobile single S.S. piston pump developing maximum 400 psi
- Light weight & compact construction
- Equipped with auto agitation system

ASPEE ASP 767 HIGH PRESSURE KNAPSACK SPRAYER**CODE: UB001B/TU26**

Technical Description	
Model	UB/001BTU 26
Engine type	2–Stroke, forced air cooled petrol engine
Displacement	25.6 cc
Carburetor	Diaphragm-type (overflow return)
Ignition system	Transistorized magneto
Starting system	Recoil starter
Air cleaner	Semi-dry
Fuel tank capacity	500 ml
Chemical tank capacity	25 ltr ± 5 %
Pump type	Positive displacement reciprocating pump (single piston double acting)
Suction /discharge capacity at no load	10 to 11 ltr/min
Normal working pressure	100 – 200 PSI
Maximum pressure	400 PSI
Weight	10 kg (approx)

ASPEE[®]**ASPEE GROUP OF COMPANIES**

ASPEE House, P. O. Box No. 7602, B. J. Patel Road, Malad (W), Mumbai 400 064. India.
Tel.: 91-22 6774 5700. Fax: 91-22 2882 2336. Email: aspee@aspee.net. Website: www.aspee.com

Important Notes: Specifications Subject To Change Without Notice.

AN ISO 9001:2008 CERTIFIED COMPANY